



FISA TEHNICA UGR 77

UGR 77 : usa de garaj tip rulou cu deschidere verticala

Destinatie: garaj rezidential/privat

Generalitati:

Caseta ALU tesit la 45 grade disponibila in dimensiuni 250x250 mm; 300x300 mm ; 360x360 mm

Ghidaje ALU dimensiune 90x35 mm

Lamele ALU cu spuma poliuretana la interior, dimensiune 77x19 mm.

Etanseitate Laterala: cheder si perii fixate pe ghidaje.

Etanseitate Inferioara : cheder "U" fixat pe ultima lamela.

Ciclu de lucru: continuu 4 min.

Dimensiuni: Customizat / La comanda, in limita :

L max: 5000 mm; **S max:** 13,5 mp conform claselor de vant **EN 13659**

Coeficient de transfer termic U: aprox 2.01 W/m²*K

Produs Standard Electric:

- Caseta
- Ghidaje
- Cover lamele 77 mm
- Ax 70 mm
- Motor Somfy cu manivela pentru actionare manuala de urgenta, cablu 1 ml


Optional Electric:

- Unitate centrala de comanda
- Arcuri antiefractie
- Buton comanda Sus/Stop/Jos
- Selector cheie
- Lamlea cu gemulete
- Lamela ALU extrudat cu fante de aerisire
- Sistem de siguranta anticadere
- Fotocelule
- Safety edge
- Lampa de avertizare




Caseta:

Caseta compusa din: Capace laterale ALU
 Fata interioara si exterioara ALU
 Ax octogonal otel 70 mm
 Role pentru ghidare covor lamele




Lamela:

Inaltime lamela 77 mm,
 Grosime lamela 19 mm
 Latime maxima 5300 mm



Ghidaje:

Latime 90 mm
 Adancime 35 mm
 Perii si cheder fixat in interior pentru etansare



Informatii tehnice:

Lamela	Dimensiune Caseta		Ghidaje	H maxim
	A	B		Electric
77	250	250	90x35	2050
	300	300		2850
	360	360		4650